



OVER/UNDER CHECKWEIGHER





CW-90

# The Checkweigher of Choice

Rice Lake's CW-90 checkweigher is designed to help speed up your weighing process and reduce production downtime, two critical factors to your company's bottom line. Ease of use, real-time data collection, and rugged stainless steel construction make the CW-90 the equipment of choice for operators, quality control, and maintenance departments. The CW-90 is competitively priced for all light industrial settings.

### **Easy to Configure**

The configuration menu of the CW-90 is accessible through the front keypad, eliminating the need to open the back of the indicator and expose the unit to moisture or contaminants. Access to these keypad controls can be limited

to meet the operator's needs. The CW-90 will store detailed information for up to 50 separate IDs, allowing for easy recall of previously saved information. An adjustable contrast display is visible in any environment.

## Simple to Maintain

The CW-90 has kept things simple to meet the needs of today's lean manufacturers. Use this checkweigher by easily watching the over/under lights. Program the unit with specified weight limits and a red light will display an underweight condition, yellow for over, and green when a target weight is reached. Rice Lake's CW-90 will help error-proof your production process and achieve your productivity goals.

Standard Size and Capacity		Dimensions	Height
5lb	5lb x 0.001lb (2.5 x 0.0005kg) 80 x 0.02oz	10in x 10in	12in
10lb	10lb x 0.002lb ( 5 x 0.001 kg) 160 x 0.05 oz	10in x 10in	12 in
25lb	25lb x 0.005lb ( 10 0.005kg) 400 x 0.1 oz	10in x 10in	12 in
25lb	25lb x 0.005lb ( 10 0.005kg) 400 x 0.1 oz	12in x 12in	12 in
50lb	50 lb x 0.01 lb (25 x 0.005 kg) 800 x 0.2 oz	12in x 12in	12 in
100lb	100lb x 0.02lb (50 x 0.01kg) 1600 x 0.5 oz	12in x 12in	12 in



### **Standard Features**

#### Indicator:

- Membrane keypad consisting of ZERO, UNITS, PRINT, TARE, OVER, UNDER, ID, TARGET, 0-9, DECIMAL, CLEAR, ENTER, MENU, POWER
- 304 stainless steel. IP66 rated
- Gore™ PreVent® breather vent
- Storage for up to 50 IDs
- Unit of Measure: kg, gm, lb, oz, lb/oz
- High-intensity LED display
- · Battery backed time and date
- Two full duplex serial ports
- Configurable print formats
- Audit trail tracking
- Optional communications: Ethernet, USB or Fiber Optic
- Four configurable Digital I/O
- Reflash memory to upgrade firmware

- Aluminum, environmentally sealed load cell
- 304 stainless steel
- Five Point overload protection

### **Specifications**

Power AC: Line voltages: 115/230 VAC

Frequency: 50/60 Hz

Fused @ 2.5A

Power Consumption: 1.5A @ 115 VAC (8W), 0.75A @ 230 VAC (8W) **Excitation Voltage:** +5VDC 8 x 350  $\Omega$  or 16 x 700  $\Omega$  load cells

Analog Signal Input Range: -0.5mV/V - 4.5mV/V

Analog Signal

0.3 µV/graduation minimum, 1.5 µV/graduation Sensitivity:

recommended

Measurement Rate: 960, 480, 240, 120, 60, 30, 15, 7.5 per second

System Linearity: +/-0.01% full scale Digital I/O: 4 channels on CPU board

Circuit Protection: RFI, EMI, EFT, ESD and surge protection

Display: Large 0.8in, 14-segment, six digit high-intensity red LED display with three color over/under bar graph

Status

Annunciators: Designators for %, kg, gm, lb, oz, center of zero, G/B, N, T, PT, neg, standstill

Operating Temperature: Legal: 14°F to 104°F (-10°C to +40°C)

Rating Material: IP66 stainless steel

Display Resolution: 100,000 graduations maximum Load Cell: Aluminum, environmentally sealed Warranty: Two-year limited warranty

### **Approvals**











GORE, GORE-TEX and design are registered trademarks of W.L. Gore & Associates, Inc.

**Phoenix Scales** 

The UK's No 1 for Service, Hire, Repair & **UKAS** Calibration

